

- VERSATILE DESIGN
- LOW AMPERAGE DRAW
- REDESIGNED SOLENOID FOR LONGER DUTY CYCLE



The PE4500 is a versatile, utility recovery tool that serves large side by side units just as well as trailer duty. Mile Marker's PE 4500 winch has been updated to include an improved solenoid design for extended duty cycle, and integrated kill switch.

## PE4500

4,500 LB Capacity  
(2041 KG)  
PN: 76-50115B



Power-In, Power-Out  
Remote Control

### PRODUCT FEATURES:

- 1.9 HP Permanent Magnet Motor
- Rugged Planetary Gear Sets
- Automatic Load Holding Brake
- Galvanized Roller Fairlead
- 80 Feet Galvanized Aircraft Cable
- Integrated Kill Switch

### PRODUCT SPECIFICATIONS:

Part Number	76-50115B
Rated line pull	4500 lbs (2041 kg)
Gear Train	3 Stage Planetary
Gear Ratio	294:1
Motor	Permanent Magnet, 1.9 hp (1.4 KW), 12 V
Control Pendant	Illuminated Joystick Remote, 12' (3.7 m)
Dimensions (LxWxH)	17.2" X 6.2" X 7.3" (436 mm X 152 mm X 185 mm)
Cable	1/4" X 80" (nominal 7,000 lbs, 3175 kg) (5.45 mm X 25.9 m)
Drum Size:	2.5" X 5.5" (63.5 mm X 140 mm)
Net weight	51 lbs (23 Kg)
Bolt Pattern	6.535" X 4.5" (4 bolts), (165.9 mm X 114.3 mm)

### PERFORMANCE:

LINE PULL		LINE SPEED		MOTOR CURRENT	
lb	kg	fpm	mpm	amps @ 12 V	
0	0	14	4.3	35	
1500	380	6.6	2	80	
2200	998	5.2	1.6	100	
3000	1361	4.6	1.4	145	
4500	2041	3.3	1	170	

Layer	RATED LINE PULL		CABLE CAPACITY	
	lb	kg	ft	meters
1	4500	2041	15	4.6
2	3880	1760	31.5	9.6
3	3420	1551	50	15.2
4	3050	1383	70	21.3
5	2750	1247	80	24.4

